

Model HA-S

Cleaning of screen rollers and gravure cylinders

Like model HA, but with the following differences:

- ▶ Rotating device for rollers/cylinders consisting of two journal supports with powered roller pairs; one journal support can be adjusted to different roller/cylinder lengths; sleeves can be supported on cover/journal disks
- ▶ 2 high-pressure nozzles on carriages and double the high-pressure pump capacity, double carriage speed, hence half the time/cylinder length for high-pressure cleaning
- ▶ Larger washing agent container

Measures and devices for a safe operation of the system

- ▶ The machine meets the requirements of all relevant EC safety directives. This is certified with a declaration of conformity and documented by means of a CE label at the machine
- ▶ All parts of the machine that come into contact with the washing agent are resistant to this agent
- ▶ Filters protect pumps, pipes, and spray nozzles from foreign matter

- ▶ Spraying in the machine is only possible after an automatic position control has signaled that the lid is closed and locked
- ▶ Level switches prevent the pumps and heating elements from running dry

Washing machine model HA-S	Size 20
Diameter max. mm	300
Weight max. kg	700
Length roller / cylinder max. mm	2000
Length sleeve max. mm	1700
Number of rollers / sleeves / cylinders	C1
Capacity of the high-pressure pump kW / l/min	3 / 10
Heating capacity kW	4

* Subject to technical changes

Size 25	Size 30	Size 35	Size 40
350	350	400	400
1000	1000	1500	1500
2500	3000	3500	4000
2200	2700	3200	3700
C1	C1	C1	C1
3 / 10	5.5 / 20	5.5 / 20	5.5 / 20
6	6	8	8

HA-S

